

TEST CERTIFICATE

This document certifies that elastomer compound

7182B

from Seals Eastern, Inc.

meets the requirements of the NORSOK M-710 Standard [Rev. 2, October 2001] with respect to rapid gas decompression (RGD) resistance at 150 barg and 100 °C.

MERL verify that O-ring seals manufactured by Seals Eastern in compound 7182B have been subjected to a multi-cycle RGD test under the following conditions.

O-ring size:	325
Test gas:	90/10 mol% CH ₄ / CO ₂
Test temperature:	100 °C
Test pressure:	150 barg
De-pressurization rate:	20 barg/minute
Test date:	6 th -20 th August 2010
Passed by:	Rhian Lewis

O-RING	MEAN CSD (MM)	SQUEEZE (%) ¹	GROOVE FILL (%)	NORSOK RATING	PASS/FAIL
1	5.28	13.7	65	0000	PASS
2	5.30	11.1	63	0000	PASS
3	5.26	11.5	66	0000	PASS

¹ radial

MATERIALS ENGINEERING RESEARCH LABORATORY LTD

Wilbury Way, Hitchin, Hertfordshire, SG4 0TW, United Kingdom. T: +44 (0) 1462 427850 F: +44 (0) 1462 427851 enquiries@merl-ltd.co.uk www.merl-ltd.co.uk